



Considerations for Survivability Mapping of Obscurant Effects

by James F. Nealon

ARL-TN-169

September 2000

Approved for public release; distribution is unlimited.

20001117 027

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21010-5423

ARL-TN-169

September 2000

Considerations for Survivability Mapping of Obscurant Effects

James F. Nealon

Survivability/Lethality Analysis Directorate, ARL

Abstract

Obscurant effects were not described in sufficient detail in the U.S. Army Research Laboratory's Survivability/Lethality Analysis Directorate (SLAD) vulnerability/lethality (VL) taxonomy. There were shortcomings in coupling the obscurant effects to target engagement, missile flyout, and probability of hit (Ph) that surfaced during modeling for the Improved Bradley Acquisition System (IBAS). This report describes the methodology used to fix these shortcomings. Obscurant effects are described and are related to effects on target engagement and hit. The report concludes with a set of logical steps and procedures to implement this methodology in a larger VL framework.

Table of Contents

	<u>Page</u>
1. Purpose.....	1
2. Background.....	1
3. Methodology Approach	1
4. Obscurant Effects.....	2
5. Trinary Logic.....	4
5.1 Elements to Hit a Target, and Obscurant Effects to Consider.....	5
5.2 Logic Steps for Engagement and Ph Determination	5
6. References	9
Distribution List	11
Report Documentation Page.....	15

INTENTIONALLY LEFT BLANK.

1. Purpose

This report comes from a request by Brian Ruth, U.S. Army Research Laboratory Survivability/Lethality Analysis Directorate (SLAD) Ballistics and NBC Division (BND), to examine how obscurant characteristics can affect probability of hit (Ph) for a tube-launched, optically tracked, wire-guided (TOW) II family missile.

2. Background

An integrated analysis program is being built for the Bradley A3 vehicle. SLAD is attempting to integrate numerous vulnerability/lethality (VL) disciplines to address effects on system survivability, via the SLAD taxonomy. Sufficient information exists for the Improved Bradley Acquisition System (IBAS) to allow calculation of probability of identification. There is insufficient information to directly calculate the ability to engage a target and successfully hit/kill it. It was necessary to review existing data for obscurant effects on missile guidance and to provide input on how to address this portion of the problem.

3. Methodology Approach

Based on existing tasks and information from field manuals, the Bradley gunner will fire the TOW II family missile when a target is identified as hostile. This requires detection, classification, and recognition first. Obscurants can affect the preceding steps by making a target have less contrast with its surroundings, suppressing its signature, and adding additional clutter to the scene. The effect, when modeled in ACQUIRE, is to shorten the distance for detection, recognitions, etc., and also to increase the time required to detect, recognize, and identify a target. ACQUIRE is a target acquisition model developed by the Night Vision/Electronic Systems Directorate of U.S. Army Communications and Electronics Command. Thus, the obscurant limit (for target engagement) is limited by obscurant characteristics optical density

([OD] and target range pairs, usually) for the 2nd-generation, forward-looking infrared (FLIR) sight.

If the gunner can identify a target as a threat (i.e., not a friendly vehicle), then it can be engaged with the missile. The gunner will need range information to adjust flight and keep track of flight time and to determine if the target is within maximum range of the missile. The laser rangefinder (LRF) is the primary means of determining range, followed by manual estimation with the reticle. The LRF is an eyesafe laser and operates at 1.54- μ m wavelength.

The gunner will need to keep the target in the FLIR's field of view to let the guidance logic track the missile flight to target. At sufficient range, the target can use obscurants in an attempt to break lock, by degrading the image presented to the gunner, for enough time to render flight commands to the missile useless. This may be a matter of seconds, and depends upon range to target, type of obscurant used, effects on presented scene, and prevailing conditions (terrain, meteorology). The cloud can degrade the guidance loop as well. Missile flight can take it into or through obscurant clouds. If the cloud is thick enough, it can reduce the beacon emissions below detection thresholds for the tracker.

4. Obscurant Effects

The discussion of OD conditions involves generic values that can be applied to a number of different advanced systems. If specific values for IBAS, Bradley A3, or the missile are available, they should be used instead of these conditions. These conditions are used to illustrate the logic involved in the methodology. OD represents a measure of how much obscurant material is present along a given line of sight (LOS), for a given time. This will vary for an LOS, depending upon weather conditions, wind, and natural cloud variations. OD (optical thickness) is defined as

$$OD = \alpha * CL, \tag{1}$$

where α is the extinction coefficient, m^2/g , and CL is the concentration-pathlength integral, g/m^2 . This relates to transmission via Beers' Law:

$$\tau = \exp(-\alpha\text{CL}) = \exp(-\text{OD}). \quad (2)$$

For many advanced weapon systems (included operator-guided), an upper value (VH) for OD was recommended, where system degradation may occur [1]. At levels beyond this value very sensitive (or very expensive), hardware may be needed for operation. A lower value (VL) of OD may also be set; below this value, most systems should operate with no effect from obscurants. For an improved FLIR, operating range and OD values should be defined in the system requirement or specification.

LRF performance depends on the receiver sensitivity, reported in decibels (db). One OD equals about 8.6 dB for two-way transmission through the cloud (4.3 dB for one-way transmission). The laser performance threshold can, therefore, be converted to an equivalent OD or transmission level. Conversely, a performance threshold (in OD) can be related to the sensitivity of the received signal in dB. Upper and lower values of OD, for laser operation, can be derived or measured, similar to that used for a FLIR.

The laser ($1.54 \mu\text{m}$) shows a spectral mismatch with the FLIR (operates at $8\text{--}12 \mu\text{m}$); for example, Table 1 shows comparisons of extinction coefficients for some common obscurants, in several bands [2]. The characteristics are also included in combined obscuration model or battlefield-induced contaminants (COMBIC), for obscurant modeling [3]. The mismatch, caused by the difference in extinction coefficients, could mean that the laser may be unable to get the range to target, if the environment contains phosphorous smoke, fog oil, or diesel-generated smoke (VEESS). The three materials have little effect in the far infrared (IR) (unless present in high OD levels), but have significant effects on the visual and near IR. It's possible, under certain conditions, to be able to see a target with the FLIR but be unable to obtain an exact range with a LRF.

Table 1. Comparison of Mass Extinction Coefficients

Obscurant Material	Wavelength Band (• m)			
	Visual 0.4–0.7	Near IR 0.7–1.2	Near IR Laser 1.06	Far IR 8–12
Phosphorous	4.08	1.77	1.37	0.29
Fog Oil	6.85	4.59	3.48	0.02
Diesel Oil (VEESS)	6.85	4.59	3.50	0.02

All three materials discussed in Table 1 are “white” (reflective/scattering) obscurants. The LRF may report a false range, if cloud elements are in the propagation path. The cloud may also scatter the laser pulse to the point where two-way attenuation drops the signal below the receiver’s threshold of detection. The target return might be rejected, in favor of a larger pulse from the cloud, unless last-pulse logic is used to find the attenuated return from the target.

Information on the guidance link can be obtained from the sight or missile specification, and from the missile beacon specification. Ratio of energy (power) can be converted to a decibel relationship and, thus, to an equivalent OD. The receiver (tracker unit) may be unable to receive enough energy, above a certain OD, to be able to recognize this as energy from the missile beacon. In this case, a missile guidance link would break and the missile could be lost. This effect may be small at short range but could be significant at extended ranges.

5. Trinary Logic

Some suggestions for “trinary logic,” on target engagement and missile hit, are also supplied. These steps are the rough design for an engagement algorithm. They reflect the steps involved for engagement and guidance, where obscurants can affect the fire-control solution or guidance

to the target. These steps can make the modeling and analysis process easier by applying obscurant effects where they have impact on the system.

5.1 Elements to Hit a Target, and Obscurant Effects to Consider.

- Identify the target: obscuration to deceive/distort, lose contrast.
- Get range to target: obscurants degrade laser return, induce false target.
- Launch missile.
- Guide missile to target,
 - obscure or distort target aspect (operator scene), and
 - degrade guidance link from missile (beacon).
- Hit target.

5.2 Logic Steps for Engagement and Ph Determination.

- Get engagement range from scenario and FMs for system.
- Set a critical range (short range) inside which the gunner will displace and evade; the threat is too close.
- While target is beyond critical range do.
 - If a gunner CANNOT identify, then done (fail to engage).

- Else, if a gunner CANNOT range to target, then use manual range estimate (reticle) (degrades ballistic solution).
- Else, if the range to target is NOT similar to known terrain features at range, then use manual estimate (degrades ballistic solution).
- Else, accept laser range to target.
- Launch/fire missile.
- While missile flight increment is less than range to target, do the following.
 - If a gunner CANNOT keep target in field of view, then missile lost.
 - Else, do the following.
 - If obscurant level is NOT above complete defeat threshold, then missile lost (guidance link defeat).
 - Else, if obscurant level is NOT below effect threshold, then missile unaffected by obscurant.
 - Else, degrade missile tracking ability by linear function of transmission level (crude, but it can be fitted to other curves or known data if available).
 - If random draw is less than tracking ability, then missile lost.
 - Else, adjust missile position by random value due to effects on beacon/receiver link.

- Increment missile flight segment toward target (velocity vector, time, and beacon shift).
- Done with flight.
- Obtain hit point by examining missile position and attitude, as adjusted by cloud effects on tracker.

INTENTIONALLY LEFT BLANK.

6. References

1. U.S. Army Materiel Systems Analysis Activity. *Smoke/Obscurants Handbook for the Electro-Optical, Millimeter Wave, and Centimeter Wave Systems Developer*. 1JTCGME-89-1, 1 September 1985.
2. U.S. Army Materiel Systems Analysis Activity. *Combat Environments Obscuration Handbook (CEOH), Volume I - Natural and Combat Induced Obscurants and Environments*. 61JTCG/ME-84-1-1, 27 May 1986.
3. U.S. Army Research Laboratory. *PcEosael Manual Version 1.0*. Adelphi, MD, 1998.

INTENTIONALLY LEFT BLANK.

NO. OF
COPIES ORGANIZATION

2 DEFENSE TECHNICAL
INFORMATION CENTER
DTIC DDA
8725 JOHN J KINGMAN RD
STE 0944
FT BELVOIR VA 22060-6218

1 HQDA
DAMO FDT
400 ARMY PENTAGON
WASHINGTON DC 20310-0460

1 OSD
OUSD(A&T)/ODDDR&E(R)
R J TREW
THE PENTAGON
WASHINGTON DC 20301-7100

1 DPTY CG FOR RDA
US ARMY MATERIEL CMD
AMCRDA
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 INST FOR ADVNCD TCHNLGY
THE UNIV OF TEXAS AT AUSTIN
PO BOX 202797
AUSTIN TX 78720-2797

1 DARPA
B KASPAR
3701 N FAIRFAX DR
ARLINGTON VA 22203-1714

1 NAVAL SURFACE WARFARE CTR
CODE B07 J PENNELLA
17320 DAHLGREN RD
BLDG 1470 RM 1101
DAHLGREN VA 22448-5100

1 US MILITARY ACADEMY
MATH SCI CTR OF EXCELLENCE
MADN MATH
MAJ HUBER
THAYER HALL
WEST POINT NY 10996-1786

NO. OF
COPIES ORGANIZATION

1 DIRECTOR
US ARMY RESEARCH LAB
AMSRL D
D R SMITH
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 DIRECTOR
US ARMY RESEARCH LAB
AMSRL DD
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 DIRECTOR
US ARMY RESEARCH LAB
AMSRL CI AI R (RECORDS MGMT)
2800 POWDER MILL RD
ADELPHI MD 20783-1145

3 DIRECTOR
US ARMY RESEARCH LAB
AMSRL CI LL
2800 POWDER MILL RD
ADELPHI MD 20783-1145

1 DIRECTOR
US ARMY RESEARCH LAB
AMSRL CI AP
2800 POWDER MILL RD
ADELPHI MD 20783-1197

4 DIR USARL
AMSRL CI LP (BLDG 305)

ABERDEEN PROVING GROUND

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OASD C3I MR BUCHHEISTER RM 3D174 6000 DEFENSE PENTAGON WASHINGTON DC 20310-6000	1	OADCSOPS FORCE DEV DIR DAMO FDZ ROOM 3A522 460 ARMY PENTAGON WASHINGTON DC 20310-0460
1	OUSD AT STRT TAC SYS DR SCHNEITER RM 3E130 3090 DEFENSE PENTAGON WASHINGTON DC 20310-3090	1	HQDA ODCSPER DAPE MR (RM 2C733) 300 ARMY PENTAGON WASHINGTON DC 20310-0300
1	OUSD AT S&T AIR WARFARE RM 3E139 R MUTZELBUG 3090 DEFENSE PENTAGON WASHINGTON DC 20301-3090	1	US ARMY MATERIEL CMD DEP CHF OF STAFF FOR RDA SCIENCE TECH ENG AMCRDA 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	OUSD AT S&T LAND WARFARE RM EB1060 A VIILU 3090 DEFENSE PENTAGON WASHINGTON DC 20310-3090	1	US ARMY MATERIEL CMD DEP CHF OF STAFF FOR RDA SCIENCE TECH ENG AMCRDA T 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	UNDER SEC OF THE ARMY DUSA OR ROOM 2E660 102 ARMY PENTAGON WASHINGTON DC 20310-0102	1	US ARMY ARMAMENT RDEC AMSTA AR TD M FISETTE BLDG 1 PICATINNY ARSENAL NJ 07806-5000
1	ASST SECY ARMY ACQUISITION LOGISTICS TCHNLGY SARD ZD ROOM 2E673 103 ARMY PENTAGON WASHINGTON DC 20310-0103	1	ECBC AMSSB RTD J ZARZYCKI 5183 BLACKHAWK RD APG MD 21010-5424
1	ASST SECY ARMY ACQUISITION LOGISTICS TCHNLGY SARD ZP ROOM 2E661 103 ARMY PENTAGON WASHINGTON DC 20310-0103	1	US ARMY MISSILE RDEC AMSMI RD W MCCORKLE RSA AL 35898-5240
1	ASST SECY ARMY ACQUISITION LOGISTICS TCHNLGY SAAL ZS ROOM 3E448 103 ARMY PENTAGON WASHINGTON DC 20310-0103	1	NATICK SOLDIER CENTER SBCN T P BRANDLER KANSAS STREET NATICK MA 01760-5056

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	US ARMY TANK AUTOMTV RDEC AMSTA TR J CHAPIN WARREN MI 48397-5000
1	US ARMY INFO SYS ENGRG CMD AMSEL IE TD F JENIA FT HUACHUCA AZ 85613-5300
1	US ARMY SIM TRNG INST CMD AMSTI CG M MACEDONIA 12350 RESEARCH PKWY ORLANDO FL 32826-3726
1	US ARMY TRADOC BATTLELAB INTEGRATION TECH B CONCEPTS DIR ATCD B FT MONROE VA 23561-5000
1	ARMY TRADOC ANL CTR ATRC W MR KEINTZ WSMR NM 88002-5502
1	US ARMY RESEARCH LAB AMSRL SL PLANS AND PGMS MGR WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL E WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL EA R FLORES WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL EM J PALOMO WSMR NM 88002-5513
1	US ARMY RESEARCH LAB AMSRL SL EI J NOWAK FT MONMOUTH NJ 07703-5602

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
	<u>ABERDEEN PROVING GROUND</u>
1	US ARMY DEV TEST COM CSTE DTC TT T APG MD 21005-5055
1	US ARMY EVALUATION CENTER CSTE AEC MR HUGHES 4120 SUSQUEHANNA AVE APG MD 21005-3013
1	US ARMY EVALUATION CENTER CSTE AEC SV D DELATTRE 4120 SUSQUEHANNA AVE APG MD 21005-3013
1	US ARMY RESEARCH LAB AMSRL SL BN D FARENWALD APG MD 21010-5423
2	US ARMY RESEARCH LAB AMSRL SL DR WADE J BEILFUSS
4	US ARMY RESEARCH LAB AMSRL SL B MS SMITH J FRANZ M VOGEL W WINNER
1	US ARMY RESEARCH LAB AMSRL SL BA M RITONDO
1	US ARMY RESEARCH LAB AMSRL SL BD J MORRISSEY
2	US ARMY RESEARCH LAB AMSRL SL BE D BELY R SANDMEYER
1	US ARMY RESEARCH LAB AMSRL SL BG A YOUNG

NO. OF
COPIES

ORGANIZATION

ABERDEEN PROVING GROUND

1	US ARMY RESEARCH LAB AMSRL SL E M STARKS
1	US ARMY RESEARCH LAB AMSRL SL EA D BAYLOR
1	US ARMY RESEARCH LAB AMSRL SL EM J FEENEY
1	US ARMY RESEARCH LAB AMSRL SL EC E PANUSKA

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 2000		3. REPORT TYPE AND DATES COVERED Final, Oct-Nov 99
4. TITLE AND SUBTITLE Considerations for Survivability Mapping of Obscurant Effects				5. FUNDING NUMBERS 665604.678
6. AUTHOR(S) James F. Nealon				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-SL-EM Aberdeen Proving Ground, MD 21010-5423				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TN-169
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)				10. SPONSORING/MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for pubic release; distribution is unlimited.				12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) <p>Obscurant effects were not described in sufficient detail in the U.S. Army Research Laboratory's Survivability/Lethality Analysis Directorate (SLAD) vulnerability/lethality (VL) taxonomy. There were shortcomings in coupling the obscurant effects to target engagement, missile flyout, and probability of hit (Ph) that surfaced during modeling for the Improved Bradley Acquisition System (IBAS). This report describes the methodology used to fix these shortcomings. Obscurant effects are described and are related to effects on target engagement and hit. The report concludes with a set of logical steps and procedures to implement this methodology in a larger VL framework.</p>				
14. SUBJECT TERMS obscurant, missile, modeling, analysis, taxonomy				15. NUMBER OF PAGES 16
				16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.